

Carotid head support (optional)

30° reverse Trendelenburg
and 15° Trendelenburg

Sonographer drop section/patient back
support and rapid release imaging drop
section (optional)

65° Fowler positioning

Bariatric capable patient
weight capacity up to 600 lbs.

Static load capacity
up to 1,000 lbs.

Lightweight/removable/
adjustable foot platform

Battery (optional)

Single pedal
braking (optional)

ADA compliant
19" to 38" at top
of mattress



Multi-modality platform



Transfer height of 19"
at top of mattress

ADA compliant 19" low height to 38" maximum height

The VasScan X helps minimize the risk of **repetitive stress injury**, **reduce exam time and improve results** while increasing **bariatric capability** and meeting the **ADA** height transfer requirement.

- 19"-38" height range meets the Americans with Disabilities Act ADA low height requirement of 17"-19" for patient transfer, while ensuring ergonomic standing posture for staff
- 30° reverse Trendelenburg increases venous pooling, prompting rapid recognition and accurate results
- The weight-bearing adjustable and removable foot platform accommodates patients of varying heights while ensuring patient safety during lower venous studies
- Bariatric capable patient weight capacity of 600 lbs establishes continuity of care
- 65° Fowler positioning increases comfort of/for patients with shortness of breath
- Optional imaging and sonographer drop sections provide unhindered access and reduce image acquisition time for echocardiograms

Optional features may be shown. Actual color may vary depending on monitor resolution and print quality.

STANDARD FEATURES

Height Adjustability:	Maximum Patient Capacity:	Fowler (Head Up):	Trendelenburg/Reverse Trendelenburg:	Foot Platform:
19" to 38"	600 lbs Maximum Load Capacity: 1,000 lbs	65°	15°/30°	Manually adjustable and removable

Control System:	Braking:	Additional Features:
Hand Controller w/ Memory positioning	Individual Locking Casters	Hand Control Storage Foley Bag/Accessory Hook

PRODUCT SPECIFICATIONS

Length:	Width:
80.5"	28"

Foam:	Electrical:	Vinyl:
California Technical Bulletin 117 - Section E	100-240VAC 50/60Hz 5A	California T.B. 117-2013 NFPA 260- Cover Fabric - Class I UFAC Fabric - Class I

CERTIFICATIONS

Industry Standards:	Warranty:	Standard Color:
UL ANSI/AAMI ES60601-1 (2005) + AMD (2012), CAN/CSA C22.2 No. 60601 (2014)	2 Years	

NEW AND IMPROVED FEATURES

ADA Compliant transfer height of 19"	Underbed lights
Maximum height of 38" ergonomically accommodates standing staff	Battery operation - avoid cords when preferred
Increased Patient weight capacity to 600 lbs	Barrier free edges with new hideaway brackets
Increased warranty to 2 years	Updated and durable hand control
Memory Positioning - Store up to 2 positions with the touch of a button	Ability to utilize both hand and foot controls
	Carotid Head Support to ergonomically accommodate all scanning needs

OPTIONAL FEATURES

Echocardiogram Drop Sections	Safety Rails w/ hideaway brackets
-Sonographer Extension	Safe-T-Wedge
-Imaging Drop Section	Pediatric/Geriatric Adapter
-2-Way Sonographer Drop Section/Patient Back Support	IV Pole and Holder
-Non-Pinch Flaps	Padded Arm Board
Single Pedal Braking	Paper Roll Holder and Cutter
Foot Controller (non-memory)	Carotid Head Support
Battery Operation - up to a full day of operation with no need for plugging in	Underbed lights